



QSARINS-Chem

Standalone Version

How To...



QSAR Research Unit in Environmental Chemistry and Ecotoxicology
Department of Theoretical and Applied Sciences (DiSTA)
University of Insubria

Authors

Nicola Chirico, Alessandro Sangion, Paola Gramatica, Linda Bertato, Ilaria Casartelli and Ester Papa

Contact: Prof. Ester Papa

QSAR Research Unit in Environmental Chemistry and Ecotoxicology
Department of Theoretical and Applied Sciences (DiSTA)
University of Insubria, Varese, Italy
<http://dunant.dista.uninsubria.it/qsar/>
e-mail: ester.papa@uninsubria.it

Acknowledgments

The authors would like to thank Stefano Cassani for the revision of the chemical structures (.hin files) of the database (till 2014). In addition helpful comments for this standalone version were provided by Jon Arnot (Arnot Research and Consulting, Inc.) and James Armitage (Armitage Environmental Sciences, Inc).

How to cite:

Please cite QSARINS-Chem standalone version in your publications as:

Nicola Chirico, Alessandro Sangion, Paola Gramatica, Linda Bertato, Ilaria Casartelli and Ester Papa, QSARINS-Chem standalone version: a new platform-independent software to profile chemicals for physico-chemical properties, fate, and toxicity, submitted to J.Comput. Chem.

We would also appreciate citations to the website: <http://dunant.dista.uninsubria.it/qsar/>

Limitations of Liability and Disclaimer of Warranty

QSARINS-Chem standalone version and the accompanying materials and manuals are provided "as they are" without warranty of any kind. The authors do not warrant, guarantee, or make any representations, either expressed or implied, regarding the use, or the results from the use of QSARINS-Chem standalone version, the accompanying materials and manuals, in terms of correctness, accuracy, reliability, currentness, or otherwise.

You assume the entire risk as to the result and performance of QSARINS-Chem standalone version.

In no event shall the authors be liable for any claim, damages or other liability, whether in an action of contract, tort or otherwise, arising from, out of or in connection with QSARINS-Chem standalone version or the use or other dealings in QSARINS-Chem standalone version, even if the authors have been advised of the possibility of such damages.

The QSARINS-Chem standalone version software, the accompanying materials and manuals are protected by copyright: 2018, University of Insubria, <http://www.uninsubria.it> - Varese, Italy.

HOW TO...

Enter user's descriptors for model predictions	3
Rearrange table columns.....	4
Resize table columns	4
Select a model	4
Select tabs on limited screen resolution	5
Show model's training descriptors or training endpoint.....	5
Sort table columns.....	5
Visualize predictions and statistics of the applied models.....	6
Visualize model's predictions graphically.....	6

Enter user's descriptors for model predictions

To enter manually the descriptors of the molecules (and optionally their experimental endpoints) in the "User descriptors" sub-tab of the "Models" tab, click on the cell, enter the data and press enter to confirm.

No.	Name	gmax	VAdjMat
1	Type name here	Type value here	Type value here

If the value inserted is problematic, the cell will turn red and a warning will be displayed in the "Status" column. Placing the mouse pointer upon the red cell for few seconds a tool tip reporting the issue will be displayed, as shown in the example below.

No.	Name	gmax	VAdjMat	nHBAcc
1	Chem_1	9.9	3.6	2
2	Chem_1	9	3	2
3	Chem_3	8	7	Type value here

Descriptor out of training range (2.6÷6.8)

It is possible to calculate the descriptors by means of the PaDEL Descriptor software (bundled with this software), and automatically import them. To accomplish this task, you have to right-click on the table and select "Import and calculate descriptors..." form the drop-down menu.

No.	Name	gmax	VAdjMat	nHBAcc
1	Type name here	Type value here	Type value here	Type value here

- Import and calculate descriptors...
- Copy
- Paste
- Delete
- Select all
- Clear all...

You will be asked for the folder containing the molecules structures files for descriptors calculation, then the PaDEL Descriptor software is automatically executed (you know that is executing because the splash screen will appear during the descriptor's calculation).

Once calculation is completed, the descriptors values will be imported automatically. Issues with molecular descriptors, if any, will be highlighted as "Warning" in the "Status" column.

Cells can be edited manually, if needed.

If data are pasted from an external source (e.g. from Excel), or a new folder is selected for additional descriptor calculation with PaDEL Descriptor, they will be automatically added below the last row (data are never overwritten).

Once data are entered either by the user or by automatic descriptors calculation, press "Apply model" to calculate model predictions. This will enable the "Predictions" and "Graphs" sub-tabs, where the model's predictions can be analyzed by the user.

Rearrange table columns

The order of the columns can be changed manually dragging the header of the column with the mouse cursor.


Resize table columns

Table columns can be resized moving the mouse cursor between the two columns headers. The mouse pointer will change as a "double arrow" indicating the possible resize direction, as shown below, then resize follows while holding and moving the left mouse key.




Select a model

To select a model click on the "Models" main tab and select the "Model selection" sub-tab. Then click on the drop-down list to choose the model, as shown in the figure below.



Select tabs on limited screen resolution

Depending on the screen resolution, it is possible that some tabs cannot be shown. In this case an arrow is displayed to the right of the screen. Clicking on the arrow a drop-down menu will appear allowing for selection of all tabs, as shown below.



Show model's training descriptors or training endpoint

To show the model's training descriptors or the training endpoint, click on the corresponding sub-tabs of the "Models" tab.

Sort table columns

To sort a column click cyclically on the column header. An arrow on the right of the column's name will appear indicating the sorting order (up arrow means ascending, down arrow means descending).

Experimental endpoint	Experimental endpoint
7.3	12
7.4	12
8.1	12

Visualize predictions and statistics of the applied models

To visualize the model's prediction click on the "Prediction" sub-tab. As in the "User descriptors" sub-tab, problematic entries will be displayed in red. Placing the mouse pointer on these values a tool-tip explaining the reason of the problem will be displayed.

Visualize model's predictions graphically


To visualize the model's predictions graphically you need first to select the sub-tab "Graphs" and then to press the "Calculate graphs" button.

To resize the graphs, move the mouse pointer upon the vertical or horizontal border separating the graphs. The mouse pointer will change as a "double arrow" indicating the possible resize direction, as shown below.



Holding the left mouse button and moving the mouse according to the suggested directions will resize the graphs.

Graph points are supported by tool-tips. Leaving the mouse pointer upon one graphic point will pop up the corresponding informative tool-tip, as shown in the figure below.



Data points are colored according to the dataset they belong to. Red is for the training set, blue for the user (prediction) set (Note: in the Insubria graph, as shown above, the color of the user set is further differentiated when the experimental endpoint value is provided for some, but not all, molecules. In this case, molecules with the experimental endpoint -“User set E”- are blue colored, while the one without the experimental endpoint -“User set N”- are colored as light blue).

It is also possible to customize the layout of the graphs. As shown in the figure above, the title, labels, grid and legend can be switched on and off and the range of the graph axes can be manually changed. Pressing the “Reset” button will reset the ranges to default.